



Aluminium Alloy Hoisting Tackle

| Item number | Model | Number of sheaves | Rated load (kN) | Outside diameter×width(mm) | Max.diameter of rope | Weight (kg) | Hoisting point type | | |
|-------------|----------|-------------------|-----------------|----------------------------|----------------------|-------------|---------------------|---|---|
| | | | | | | | G | H | B |
| 11101 | QHN1-1k | 1 | 10 | Φ100×31 | Φ7.7 | 1.8 | G | H | |
| 11102 | QHN1-2 | 2 | 10 | Φ80×27 | Φ6 | 1.8 | G | H | |
| 11103 | QHN1-3 | 3 | 10 | Φ80×27 | Φ6 | 2.1 | G | H | |
| 11111 | QHN2-1K | 1 | 20 | Φ120×35 | Φ9.3 | 2.2 | G | H | B |
| 11112 | QHN2-2 | 2 | 20 | Φ100×31 | Φ7.7 | 2.6 | G | H | |
| 11113 | QHN2-3 | 3 | 20 | Φ100×31 | Φ7.7 | 3.7 | G | H | |
| 11121 | QHN3-1K | 1 | 30 | Φ150×39 | Φ11 | 3.4 | G | H | B |
| 11122 | QHN3-2 | 2 | 30 | Φ120×35 | Φ9.3 | 4.5 | G | H | |
| 11123 | QHN3-3 | 3 | 30 | Φ100×31 | Φ7.7 | 4.6 | G | H | |
| 11131 | QHN5-1K | 1 | 50 | Φ166×40 | Φ13 | 5.2 | G | H | B |
| 11133 | QHN5-2 | 2 | 50 | Φ150×39 | Φ11 | 5.5 | G | H | |
| 11134 | QHN5-3 | 3 | 50 | Φ120×35 | Φ9.3 | 5.1 | G | H | |
| 11141 | QHN8-1K | 1 | 80 | Φ205×49 | Φ17 | 7.2 | G | H | B |
| 11142 | QHN8-2 | 2 | 80 | Φ166×40 | Φ13 | 8.3 | G | H | |
| 11143 | QHN8-3 | 3 | 80 | Φ150×39 | Φ11 | 7.9 | G | H | |
| 11151 | QHN10-1K | 1 | 100 | Φ246×60 | Φ18.5 | 11.4 | G | | B |
| 11152 | QHN10-2 | 2 | 100 | Φ166×40 | Φ13 | 10.2 | | H | |
| 11153 | QHN10-3 | 3 | 100 | Φ150×39 | Φ11 | 11.7 | | H | |
| 11161 | QHN15-1K | 1 | 150 | Φ280×65 | Φ21.5 | 12.1 | | | B |
| 11162 | QHN15-2 | 2 | 150 | Φ205×49 | Φ17 | 12.8 | | H | |
| 11163 | QHN15-3 | 3 | 150 | Φ166×40 | Φ13 | 11.8 | | H | |
| 11164 | QHN15-4 | 4 | 150 | Φ150×39 | Φ11 | 13.9 | | H | |

Uses:Applied in line construction for lifting weight.

Features:Adopt aluminum alloy side panel and MC nylon sheave .so it is light in weight .the single sheave hoisting tackle is open style.



Iron Hoisting Block

| Item number | Model | Number of sheaves | Rated load (kN) | Outside diameter×width(mm) | Max. diameter of rope (mm) | Weight (kg) | Hoisting point type | | |
|-------------|---------|-------------------|-----------------|----------------------------|----------------------------|-------------|---------------------|---|---|
| | | | | | | | G | H | B |
| 11181 | QH1-1K | 1 | 10 | Φ100×31 | Φ7.7 | 2.8 | G | H | |
| 11182 | QH1-2 | 2 | 10 | Φ80×27 | Φ6 | 2.8 | G | H | |
| 11183 | QH1-3 | 3 | 10 | Φ80×27 | Φ6 | 4.1 | G | H | |
| 11191 | QH2-1K | 1 | 20 | Φ120×35 | Φ9.3 | 4.2 | G | H | B |
| 11192 | QH2-2 | 2 | 20 | Φ100×31 | Φ7.7 | 4.2 | G | H | |
| 11193 | QH2-3 | 3 | 20 | Φ100×31 | Φ7.7 | 6 | G | H | |
| 11201 | QH3-1K | 1 | 30 | Φ150×39 | Φ11 | 7 | G | H | B |
| 11202 | QH3-2 | 2 | 30 | Φ120×35 | Φ9.3 | 5.3 | G | H | |
| 11203 | QH3-3 | 3 | 30 | Φ100×31 | Φ7.7 | 6.5 | G | H | |
| 11211 | QH5-1K | 1 | 50 | Φ166×40 | Φ13 | 9.6 | G | H | B |
| 11212 | QH5-2 | 2 | 50 | Φ150×39 | Φ11 | 10.8 | G | H | |
| 11213 | QH5-3 | 3 | 50 | Φ120×35 | Φ9.3 | 7.7 | G | H | |
| 11221 | QH8-1K | 1 | 80 | Φ205×50 | Φ17 | 12.5 | G | H | B |
| 11222 | QH8-2 | 2 | 80 | Φ166×40 | Φ13 | 17 | G | H | |
| 11223 | QH8-3 | 3 | 80 | Φ150×39 | Φ11 | 17.5 | G | H | |
| 11231 | QH10-1K | 1 | 100 | Φ246×60 | Φ18.5 | 25 | G | | B |
| 11232 | QH10-2 | 2 | 100 | Φ166×40 | Φ13 | 18.5 | | H | |
| 11233 | QH10-3 | 3 | 100 | Φ150×39 | Φ11 | 20 | | H | |
| 11241 | QH15-1K | 1 | 150 | Φ280×65 | Φ21.5 | 34 | | | B |
| 11242 | QH15-2 | 2 | 150 | Φ205×50 | Φ17 | 22 | | H | |
| 11243 | QH15-3 | 3 | 150 | Φ166×40 | Φ13 | 26 | | H | |
| 11244 | QH15-4 | 4 | 150 | Φ150×39 | Φ11 | 30 | | H | |
| 11248 | QH20-4 | 4 | 200 | Φ205×50 | Φ17 | 50 | | H | |

Uses:To erect pole and tower ,line construction ,hoist devices ,etc

Features:Hoisting point type:hook style (G), round eye style (H), clevis type (B)





Aluminium Hoisting Tackle

| Item number | Model | Style | Rated load (kN) | Outside diameter ×width (mm) | Weight (kg) |
|-------------|-----------|------------------------|-----------------|------------------------------|-------------|
| 11251 | QH1GL-1 | Monosheave ,open ,hook | 10 | Φ100×31 | 2.2 |
| 11252 | QH2GL-1 | Twin –sheave ,hook | 10 | Φ80×27 | 2.3 |
| 11253 | QH2HL-1 | Twin –sheave, ring | 10 | Φ80×27 | 1.9 |
| 11261 | QH3GL-1.5 | Tri –sheave, hook | 15 | Φ80×27 | 3 |
| 11262 | QH3HL-1.5 | Tri –sheave, ring | 15 | Φ80×27 | 2.6 |
| 11271 | QH3GL-2 | Tri –sheave, hook | 20 | Φ100×31 | 4.5 |
| 11272 | QH3HL-2 | Tri –sheave, ring | 20 | Φ100×31 | 3.5 |
| 11273 | QH2GL-2 | Twin –sheave, hook | 20 | Φ100×31 | 3.6 |
| 11274 | QH2HL-2 | Twin –sheave, ring | 20 | Φ100×31 | 3 |
| 11275 | QH1HL-2 | Monosheave, open, ring | 20 | Φ120×35 | 3.4 |



Dual-Sheave Hoisting Tackle

| Item number | Model | Rated load (kN) | Diameter of rope (mm) | Weight (kg) | Hook | Ring |
|-------------|---------|-----------------|-----------------------|-------------|------|------|
| 11281 | QHS2-3 | 30 | ≤Φ9.3 | 6.3 | G | H |
| 11282 | QHS2-5 | 50 | ≤Φ11 | 13 | G | H |
| 11283 | QHS2-8 | 80 | ≤Φ13 | 18 | G | H |
| 11284 | QHS2-10 | 100 | ≤Φ13 | 21 | G | H |

Feature:The block has openings in both sides ,so it is convenient to assemble and disassemble the steel wire rope .

Notes:Hoisting point type : hook style (G), round eye style (H)

